




МОДЕЛЬ	ГОСТ Р ЕН				РАЗМЕРЫ	РАЗМЕРЫ				Количество точек крепления	140 кг	Допущен к работе во взрывоопасных зонах	Огнестойкость в соответствии с ГОСТ Р ЕН 358.	Вес (г)
	361	358	813	1497		Охват грудной клетки	Охват талии	Охват бедер	Охват туловища					
	A (см)	B (см)	C (см)	D (см)										
P 01					M-XL	60-120	-	50-70	55-75	1		●		640
					XXL	75-150	-	60-85	65-85					660
P 01B	●				M-XL	60-120	-	50-70	55-80	1				650
					XXL	75-140	-	60-85	65-95					670
P 01S	●				M-XL	60-120	-	50-70	55-75	1		●		690
					XXL	75-150	-	60-85	65-85					710
P 02	●	●			M-XL	60-120	90-115	50-70	55-75	2		●		1050
					XXL	75-150	100-135	60-85	65-85					1150
P 02S	●	●			M-XL	60-120	90-115	50-70	55-75	2		●		1100
					XXL	75-150	100-135	60-85	65-85					1200
P 03	●				M-XL	60-120	-	50-70	55-75	2	●	●		690
					XXL	75-150	-	60-85	65-85					700
P 03AL	●				M-XL					2				670
					XXL									680
P 03S	●				M-XL	60-120	-	50-70	55-75	2		●		730
					XXL	75-150	-	60-85	65-85					740
P 05	●	●			M-XL	60-120	90-115	50-70	55-75	3	●	●		1120
					XXL	75-150	100-135	60-85	65-85					1220
P 05S	●	●			M-XL	60-120	90-115	50-70	55-75	3		●		1160
					XXL	75-150	100-135	60-85	65-85					1260
P 10	●				M-XL	75-120	-	50-80	55-80	1		●		870
					XXL	80-140	-	75-95	65-95					900
P 10A	●				M-XL					1				920
					XXL									1000
P 10F	●				M-XL					3				1000
					XXL									1050
P 10R	●			●	M-XL					3		●		1460
					XXL									1600
P 10R HV	●			●	M-XL					3				
					XXL									




МОДЕЛЬ	ГОСТ Р ЕН				РАЗМЕРЫ	РАЗМЕРЫ				Количество точек крепления	140 кг	Допущен к работе во взрывоопасных зонах	Огнестойкость в соответствии с ГОСТ Р ЕН 358.	Вес (г)
	361	358	813	1497		Охват грудной клетки A (см)	Охват талии B (см)	Охват бедер C (см)	Охват туловища D (см)					
P 11	•				M-XL					2	•		1100	
					XXL								1150	
P 11C	•				M-XL					2	•		1100	
					XXL								1200	
P 12PRO	•				M-XL					1	•		1115	
					XXL								1165	
P 14R	•				M-XL	75-120	-	50-80	55-80	1			1600	
					XXL	80-140	-	75-95	65-95				1720	
P 15E	•				M-XL					1			1220	
					XXL								1290	
P 16	•		•		M-XL					2			1360	
					XXL								1430	
P 20	•	•			M-XL	75-120	90-120	50-80	55-80	2	•		1350	
					XXL	80-140	100-130	75-95	65-95				1450	
P 20C	•			•	M-XL					2			1600	
					XXL								1690	
P 22PRO	•	•			M-XL					2	•		1450	
					XXL								1550	
P 30	•				M-XL	75-120	-	50-80	55-80	2	•	•	1010	
					XXL	80-140	-	75-100	65-95				1080	
P 30A	•				M-XL					2			1135	
					XXL								1205	
P 30C	•				M-XL					2	•		1100	
					XXL								1180	
P 30E	•				M-XL					2	•		1235	
					XXL								1305	
P 30EC	•				M-XL					2	•		1305	
					XXL								1395	
P 30HV+	•				M-XL	75-120	-	50-80	55-80	2			1000	
					XXL	80-140	-	75-100	65-95				1060	




МОДЕЛЬ	ГОСТ Р ЕН				РАЗМЕРЫ	РАЗМЕРЫ				Количество точек крепления	140 кг Допущен к работе во взрывоопасных зонах	Огнестойкость в соответствии с ГОСТ Р ЕН 358.	Вес (г)	
	361	358	813	1497		РАЗМЕРЫ	Охват грудной клетки A (см)	Охват талии B (см)	Охват бедер C (см)					Охват туловища D (см)
P 30N	•				M-XL	75-120	-	50-80	55-80	2	•	•	•	1030
					XXL	80-140	-	75-100	65-95					1090
P 30NX	•			•	M-XL	75-120	-	50-80	55-80	2	•	•	•	1065
					XXL	80-140	-	75-100	65-95					1115
P 32PRO	•				M-XL					2		•		1650
					XXL									1750
P 33EL	•				M-XL	75-120	-	50-70	55-75	2				1500
					XXL	80-140	-	65-90	65-85					1660
P 34EL	•				M-XL	75-120	-	60-75	55-75	1				1600
					XXL	80-140	-	65-90	65-85					1700
P 35	•				M-XL	75-120	-	50-70	55-75	2				1150
					XXL	80-140	-	65-90	65-85					1200
P 35C	•				M-XL					2				1220
					XXL									1270
P 35CR	•			•	M-XL					3	•			1395
					XXL									1475
P 35CR HV	•			•	M-XL					2				
					XXL									
P 35E	•				M-XL					2				1220
					XXL									1270
P 36	•				M-XL	75-120	-	50-70	55-75	2				1080
					XXL	80-140	-	65-90	65-85					1130
P 36AL	•				M-XL					2				1065
					XXL									1135
P 36C	•				M-XL					2				1100
					XXL									1160
P 37	•				M-XL					1				1270
					XXL									1420
P 37C	•				M-XL					1				1330
					XXL									1470
P 37CR	•			•	M-XL					2				1495
					XXL									1655
P 37R	•			•	M-XL					2				1435
					XXL									1595



МОДЕЛЬ	ГОСТ Р ЕН				РАЗМЕРЫ	РАЗМЕРЫ				Количество точек крепления	140 кг	Допущен к работе во взрывоопасных зонах	Огнестойкость в соответствии с ГОСТ Р ЕН 358.	Вес (г)
	361	358	813	1497		РАЗМЕРЫ	Охват грудной клетки A (см)	Охват талии B (см)	Охват бедер C (см)					
P 39	●				M-XL					2				1380
					XXL									1520
P 39C	●				M-XL					2				1445
					XXL									1585
P 39CR	●			●	M-XL					3				1610
					XXL									1760
P 39R	●			●	M-XL					3				1550
					XXL									1690
P 40	●				M-XL	75-120	-	50-80	55-80	2				1050
					XXL	80-140	-	75-95	65-95					1200
P 40A	●				M-XL					2				1260
					XXL									1310
P 40C	●				M-XL					2				1090
					XXL									1240
P 40HV	●				M-XL					2				
					XXL									
P 42	●	●			M-XL	75-120	90-120	50-80	55-80	3		●		1530
					XXL	80-140	100-130	75-95	65-95					1750
P 42HV	●	●			M-XL					3				
					XXL									
P 50	●	●			M-XL	75-120	90-120	50-80	55-80	3	●	●		1640
					XXL	80-140	100-130	75-100	65-95					1790
P 50HV+	●	●			M-XL					3				1460
					XXL									1600
P 50NX	●	●			M-XL					3	●	●	●	1685
					XXL									1755
P 50N ISOL	●	●			M-XL					3	●	●	●	1690
					XXL									1790
P 51E	●	●			M-XL	75-120	90-120	50-80	55-80	3		●		1945
					XXL	80-140	100-140	75-100	65-95					2080
P 51E ISOL	●	●			M-XL	75-120	90-120	50-80	55-80	3		●		2105
					XXL	80-140	100-140	75-100	65-95					2240
P 52PRO	●	●			M-XL					3		●		1650
					XXL									1750



МОДЕЛЬ	ГОСТ Р ЕН				РАЗМЕРЫ	РАЗМЕРЫ				Количество точек крепления	140 кг Допущен к работе во взрывоопасных зонах Огнестойкость в соответствии с ГОСТ Р ЕН 358.	Вес (г)
	361	358	813	1497		Охват грудной клетки A (см)	Охват талии B (см)	Охват бедер C (см)	Охват туловища D (см)			
P 56	•	•			M-XL					3		1500
					XXL							
P 56AL2	•	•			M-XL					3		2380
					XXL							
P 56C	•	•			M-XL					3		1530
					XXL							
P 58C	•	•			M-XL					3		2030
					XXL							
P 60	•	•			M-XL	75-120	90-120	55-70	55-80	3	•	1720
					XXL	80-140	100-130	65-80	65-95			
P 60E	•	•			M-XL	75-120	90-120	55-70	55-80	3	•	1880
					XXL	80-140	100-130	65-80	65-95			
P 61	•	•			M-XL	75-120	90-120	55-70	55-80	3	•	1880
					XXL	80-140	100-130	65-80	65-95			
P 61C	•	•			M-XL					3		2105
					XXL							
P 61E	•	•			M-XL	75-120	90-120	55-70	55-80	3	•	1880
					XXL	80-140	100-130	65-80	65-95			
P 61EC	•	•			M-XL					3		2105
					XXL							
P 62EC	•	•			M-XL					3		2370
					XXL							
P 70	•	•	•		M-XL	75-120	80-130	50-70	55-75	3	•	1660
					XXL	80-140	120-150	70-90	65-85			
P 70C	•	•	•		M-XL					4	•	1660
					XXL							
P 71	•	•	•		M-XL	75-120	80-130	50-70	55-75	4		1660
					XXL	80-140	120-150	70-90	65-85			
P 71C	•	•	•		M-XL					4	•	1720
					XXL							
P 71CR	•	•	•	•	M-XL					5	•	1780
					XXL							
P 71E	•	•	•		M-XL					4	•	1720
					XXL							



МОДЕЛЬ	ГОСТ Р ЕН				РАЗМЕРЫ				Количество точек крепления	140 кг	Допущен к работе во взрывоопасных зонах	Огнестойкость в соответствии с ГОСТ Р ЕН 358.	Вес (г)	
	361	358	813	1497	РАЗМЕРЫ	Охват грудной клетки A (см)	Охват талии B (см)	Охват бедер C (см)						Охват туловища D (см)
P 73	●	●	●		M-XL					4	●			1780
					XXL									1890
P 80	●	●	●		M-XL	75-120	85-110	50-70	55-75	4				1720
					XXL	80-140	90-130	70-90	65-85					1800
P 80E	●	●	●		M-XL	75-120	85-110	50-70	55-75	4	●	●		1780
					XXL	80-140	90-130	70-90	65-85					1860
P 80E ISOL	●	●	●		M-XL					4				1800
					XXL									1920
P 81	●	●	●		M-XL	75-120	80-120	50-75	55-75	4	●			1890
					XXL	80-140	90-140	70-90	65-85					1980
P 81D	●	●	●		M-XL					4				1810
					XXL									1900
P 86R	●	●		●	M-XL					4	●			1820
					XXL									1960
P 87R	●	●		●	M-XL					4	●			2540
					XXL									2750
P 87R HV	●	●	●		M-XL					4				
					XXL									
P 90	●	●	●		M-XL					4	●	●		1950
					XXL									2030
P 90C	●	●	●		M-XL					4	●			1950
					XXL									2030